

Battery Insulator models

Model	Max current	Voltage range	Number of inputs	Number of outputs	Dimensions in mm (w x d x h)
CORUS 100-1E-2IG	100 Amp	8 - 30 VDC	1 (Ø M6)	2 (Ø M6)	146 x 85 x 97 mm
CORUS 100-1E-3IG	100 Amp	8 - 30 VDC	1 (Ø M6)	3 (Ø M6)	146 x 85 x 158 mm
CORUS 150-1E-2IG	150 Amp	8 - 30 VDC	1 (Ø M8)	2 (Ø M6)	146 x 85 x 97 mm
CORUS 150-1E-3IG	150 Amp	8 - 30 VDC	1 (Ø M8)	3 (Ø M6)	146 x 85 x 158 mm
CORUS 180-1E-2IG	180 Amp	8 - 30 VDC	1 (Ø M8)	2 (Ø M8)	146 x 85 x 97 mm
CORUS 180-1E-3IG	180 Amp	8 - 30 VDC	1 (Ø M8)	3 (Ø M8)	146 x 85 x 158 mm
CORUS 230-1E-2IG	230 Amp	8 - 30 VDC	1 (Ø M8)	2 (Ø M8)	146 x 85 x 97 mm
CORUS 250-1E-3IG	250 Amp	8 - 30 VDC	1 (Ø M8)	3 (Ø M8)	146 x 85 x 158 mm
CORUS 100-2E-3IG	100 Amp	8 - 30 VDC	2 (Ø M6)	3 (Ø M6)	146 x 85 x 158 mm

Battery Guard models

VLTG 70	70 Amp	8 - 30 VDC	1 (Ø M6)	1 (Ø M6)	100 x 89,2 x 43 mm
VTG 200	200 Amp	8 - 30 VDC	1 (Ø M8)	1 (Ø M8)	146 x 85 x 97 mm